

UC Engine Assembly with UC-ENGINE-Z, HD-CONV-USB-200, & UC-CONN-HD



- *Preassembled mounting bracket with UC Engine, HDMI® to USB Converter, and EDID Emulator*
- *Security covers conceal and protect connections*
- *Multiple cable tie points with reusable cable ties*
- *Mounts cleanly to the wall or behind a display device*
- *Includes VESA® 100, 200, or 300 mounting holes for left or right side mounting to the back of the display*
- *Single-gang cutout accommodates an AC outlet or AV/data jack (in-wall box or mud-ring required)*

The UC Engine Assembly (UC-BRKT-100-Z-ASSY) streamlines the installation of a [Crestron Flex](#) UC system by incorporating the UC-ENGINE-Z, HD-CONV-USB-200, and UC-CONN-HD together on one convenient mounting bracket.

The complete assembly can be mounted on the wall, or it can be attached to the rear of the display device. Attachment to the display is accomplished using two of the four bolts that also affix the display to a VESA® compliant display mount. The assembly bracket includes mounting holes on its left and right side edges, spaced at 100, 200, and 300 mm vertically, to allow for attachment to either side of a mounting plate on the rear of a display.

To manage wiring and conceal connections for a clean, secure installation, a 1-gang sized cutout at the lower right-hand corner allows for mounting over a flush wall-mounted electrical box. The box may be used for an AC outlet or a wall plate containing AV and data jacks.

This product is sold exclusively as part of a complete [Crestron Flex](#) system kit.

Specifications

Included Components

UC-ENGINE-Z: UC Engine for Zoom Rooms™ video

HD-CONV-USB-200: HDMI to USB 3.0 converter for content ingest

UC-CONN-HD: EDID emulator for UC Engine display output

USB cable for HDMI to USB converter, USB 3.0 Type-B male to Type-A male, 3 ft (1 m)

Mounting bracket

Construction

Composition: Metal mounting bracket, black; preassembled with components, cable management, and security covers attached

Wall Mounting: Surface wall mountable behind the display device using screws and anchors

Display Mounting: VESA compliant display mount; attachable to the rear of the display device (VESA display mount not included)

Dimensions

Height: 16.00 in. (407 mm)

Width: 14.00 in. (356 mm)

Depth: 1.62 in. (41 mm)

Crestron and the Crestron logo are either trademarks or registered trademarks of Crestron Electronics, Inc. in the United States and/or other countries. HDMI is either a trademark or registered trademark of HDMI Licensing LLC in the United States and/or other countries. Zoom Rooms is either a trademark or registered trademark of Zoom Video Communications, Inc. in the United States and/or other countries. VESA is either a trademark or registered trademark of Video Electronics Standards Association in the United States and/or other countries. Other trademarks, registered trademarks, and trade names may be used in this document to refer to either the entities claiming the marks and names or their products. Crestron disclaims any proprietary interest in the marks and names of others. Crestron is not responsible for errors in typography or photography. Specifications are subject to change without notice.

Specifications are subject to change without notice.

©2019 Crestron Electronics, Inc.

Rev 07/19/19

AUDIO VIDEO SUPPLY

UC-BRKT-100-Z-ASSY

UC Engine Assembly with UC-ENGINE-Z, HD-CONV-USB-200, & UC-CONN-HD

